

PI-778 <規格表>

表中より、W寸法・A寸法の表記を削除

型式 Type	No.	D	指定1mm単位		M(並目) 選択	V	H	T	m ₁	d ₁	d ₂	h	P.C.D.	¥基準単価 ラウンドタイプ		
			Y	F										FXFC	PFXFC	SFXFC
ラウンドタイプ FXFC PFXFC SFXFC	6	6	12~60	5~100	4 5 6	8	26	10	M 4	6.5	3.5	3.5	17	1,480	1,760	2,210
	6A					32	23						1,840	2,200	2,750	
	8					28	19						1,590	1,910	2,390	
	8A	36			26	2,130	2,550		3,190							
	10	13			32	23	1,680		2,030	2,530						
	10A	40			30	2,410	2,900		3,640							
	12	12	15	36	26	1,900	2,270	2,840								
	13	13	16	38	27	2,130	2,550	3,190								
	15	15	18	40	30	2,220	2,660	3,340								
	16	16	8 10 12 (15)	19	42	31	2,600	3,140	3,940							
	17	17	20	44	32	2,760	3,340	4,190								
	18	18	10 12 (15) 16	21	46	34	2,830	3,410	4,260							
	20	20	24	48	36	2,850	3,430	4,280								
	22	22	26	50	39	3,420	4,110	5,130								
	25	25	29	54	42	3,370	4,050	5,060								
	30	30	34	62	49	4,010	4,800	6,000								
	35	35	39	70	55	4,500	7,840	—								
	40	40	44	80	63	6,670	9,880	—								
	50	50	54	90	73	8,000	13,690	—								

◎Mの()付寸法、M15・M25は細目ねじとなります。MをMSCに変えてご指定ください。◎取付穴は、表・裏両方から取付けられるよう、タップ加工及びザグリ加工がされています。

<訂正用>

型式 Type	No.	D	指定1mm単位		M(並目) 選択	V	H	T	m ₁	d ₁	d ₂	h	P.C.D.	¥基準単価 ラウンドタイプ		
			Y	F										FXFC	PFXFC	SFXFC
ラウンドタイプ FXFC PFXFC SFXFC	6	6	12~60	5~100	4 5 6	8	26	10	M 4	6.5	3.5	3.5	17	1,480	1,760	2,210
	6A					32	23						1,840	2,200	2,750	
	8					28	19						1,590	1,910	2,390	
	8A	36			26	2,130	2,550		3,190							
	10	13			32	23	1,680		2,030	2,530						
	10A	40			30	2,410	2,900		3,640							
	12	12	15	36	26	1,900	2,270	2,840								
	13	13	16	38	27	2,130	2,550	3,190								
	15	15	18	40	30	2,220	2,660	3,340								
	16	16	8 10 12 (15)	19	42	31	2,600	3,140	3,940							
	17	17	20	44	32	2,760	3,340	4,190								
	18	18	10 12 (15) 16	21	46	34	2,830	3,410	4,260							
	20	20	24	48	36	2,850	3,430	4,280								
	22	22	26	50	39	3,420	4,110	5,130								
	25	25	29	54	42	3,370	4,050	5,060								
	30	30	34	62	49	4,010	4,800	6,000								
	35	35	39	70	55	4,500	7,840	—								
	40	40	44	80	63	6,670	9,880	—								
	50	50	54	90	73	8,000	13,690	—								

◎Mの()付寸法、M15・M25は細目ねじとなります。MをMSCに変えてご指定ください。◎取付穴は、表・裏両方から取付けられるよう、タップ加工及びザグリ加工がされています。