

Type	型式		W	A	B	T ₁	T ₂	T ₃	h	L	P	M	d	付属ボルト	取付穴数	¥基準単価
	ベルト種類	ベルト呼び幅														
XL		025	6.4	66	24	6	4.5	2.10	1.30	56	13	M4	4.5	M4-10	6	1,240
		037	9.5		26						16					1,240
		050	12.7		30						20					1,280
L		050	12.7	124	32	8	5.5	3.33	2.05	111	21	M5	5.5	M5-12	8	1,680
		075	19.1		38						27					1,720
		100	25.4		46						34					1,750
H		075	19.1	165	38	10	6.5	4.15	2.55	147	27	M5	5.5	M5-14	8	2,370
		100	25.4		46						34					2,390
		150	38.1		58						46					2,500
S3M		060	6	39	18	4	3.5	1.94	1.25	31	11	M3	3.4	M3-6	6	1,090
		100	10		26						17					1,370
		150	15		32						22					1,390
S5M		250	25	65	42	6	5.5	3.14	2.00	51	32	M4	4.5	M4-10	6	1,520
		150	15		34						23					1,670
		250	25		44						33					1,710
S8M		300	30	104	50	8	6.5	4.72	3.00	84	38	M5	5.5	M5-12	8	1,750
		400	40		60						48					1,780
		070	7		20						13					1,460
MA3		100	10	39	24	4	3.5	1.8	1.1	31	16	M3	3.4	M3-6	6	1,480
		150	15		29						21					1,490
		100	10		26						17					1,560
MA5		150	15	65	32	6	5.5	2.9	1.7	51	22	M4	4.5	M4-10	6	1,580
		250	25		37						32					1,820
		150	15		34						23					2,020
MA8		200	20	104	39	8	6.5	4.3	2.8	84	28	M5	5.5	M5-12	8	2,060
		250	25		45						33					2,100
		400	40		60						48					2,130
T5		100	10	65	26	6	4.5	2.20	1.40	51	17	M4	4.5	M4-10	6	1,380
		150	15		32						22					1,400
		200	20		38						27					1,490
T10		250	25	130	43	8	6.5	4.30	2.70	111	32	M5	5.5	M5-12	8	1,540
		150	15		34						23					1,840
		200	20		40						28					1,870
AT5		250	25	65	44	6	4.5	2.6	1.40	51	33	M4	4.5	M4-10	6	1,910
		300	30		50						38					1,960
		400	40		60						48					2,080
AT10		500	50	130	70	8	6.5	4.30	2.70	111	58	M5	5.5	M5-12	8	2,180
		150	15		32						22					1,400
		200	20		40						28					1,870
AT10		250	25	130	44	8	6.5	4.30	2.70	111	33	M5	5.5	M5-12	8	1,910

TBCK
(①+②)

① 本商品はオープンエンドベルト(ウレタンタイプ)に適合するよう設計されております。他ベルトとのかみ合わせの場合は、ベルト背厚と本商品寸法を確認のうえご使用ください。

② 歯形はタイミングベルトおよびオープンエンドベルトに準じます。A寸は6歯(金具)噛み合せの設定です。

<訂正用>

Type	型式		W	A	B	T ₁	T ₂	T ₃	h	L	P	M	d	付属ボルト	取付穴数	¥基準単価
	ベルト種類	ベルト呼び幅														
XL		025	6.4	66	24	6	4.5	2.10	1.30	56	13	M4	4.5	M4-10	6	1,240
		037	9.5		26						16					1,240
		050	12.7		30						20					1,280
L		050	12.7	124	32	8	5.5	3.33	2.05	111	21	M5	5.5	M5-12	8	1,680
		075	19.1		38						27					1,720
		100	25.4		46						34					1,750
H		075	19.1	165	38	10	6.5	4.15	2.55	147	27	M5	5.5	M5-14	8	2,370
		100	25.4		46						34					2,390
		150	38.1		58						46					2,500
S3M		060	6	39	18	4	3.5	1.94	1.25	31	11	M3	3.4	M3-6	6	1,090
		100	10		26						17					1,370
		150	15		32						22					1,390
S5M		250	25	65	42	6	5.5	3.14	2.00	51	32	M4	4.5	M4-10	6	1,520
		150	15		34						23					1,670
		250	25		44						33					1,710
S8M		300	30	104	50	8	6.5	4.72	3.00	84	38	M5	5.5	M5-12	8	1,750
		400	40		60						48					1,780
		070	7		20						13					1,460
MA3		100	10	39	24	4	3.5	1.8	1.1	31	16	M3	3.4	M3-6	6	1,480
		150	15		29						21					1,490
		100	10		26						17					1,560
MA5		150	15	65	32	6	5.5	2.9	1.7	51	22	M4	4.5	M4-10	6	1,580
		250	25		37						32					1,820
		150	15		34						23					2,020
MA8		200	20	104	39	8	6.5	4.3	2.8	84	28	M5	5.5	M5-12	8	2,060
		250	25		45						33					2,100
		400	40		60						48					2,130
T5		100	10	65	26	6	4.5	2.20	1.40	51	17	M4	4.5	M4-10	6	1,380
		150	15		32						22					1,400
		200	20		38						27					1,490
T10		250	25	130	43	8	6.5	4.30	2.70	111	32	M5	5.5	M5-12	8	1,540
		150	15		34						23					1,840
		200	20		40						28					1,870
AT5		250	25	65	44	6	4.5	2.6	1.40	51	33	M4	4.5	M4-10	6	1,910
		300	30		50						38					1,960
		400	40		60						48					2,080
AT10		500	50	130	70	8	6.5	4.30	2.70	111	58	M5	5.5	M5-12	8	2,180
		150	15		32						22					1,400
		200	20		40						28					1,870
AT10		250	25	130	44	8	6.5	4.30	2.70	111	33	M5	5.5	M5-12	8	1,910

TBCK
(①+②)

① 本商品はオープンエンドベルト(ウレタンタイプ)に適合するよう設計されております。他ベルトとのかみ合わせの場合は、ベルト背厚と本商品寸法を確認のうえご使用ください。

② 歯形はタイミングベルトおよびオープンエンドベルトに準じます。A寸は6歯(金具)噛み合せの設定です。