

規格表の型式 FEXB を FXEB に訂正。

型式		D	指定1mm単位		M (並目) 選択	V	H	T	m1	d1	h	P.C.D.	W	A	Y基準単位										
Type	No.		Y	F											ラウンドタイプ			コンパクトタイプ							
															FXFB	PFXFB	SFXFB	FEXB	PFXEB	SFXEB					
ラウンドタイプ FXFB PFXFB SFXFB コンパクトタイプ FEXB PFXEB SFXEB	6	6	12~60	5~100	3	8	26	10	M 4	6.5	3.5	17	14	17	1,480	1,760	2,210	2,380	2,860	3,570					
	6A					32	23					—	—	1,840	2,200	2,750	—	—							
	8					28	19					15	19	1,590	1,910	2,390	2,500	3,000	3,750						
	8A					36	—					—	—	2,130	2,550	3,190	—	—							
	10A	10			10~150	4 5 6	13		40	15	M 4	6.5	3.5	23	16	23	1,680	2,030	2,530	2,600	3,120	3,900			
	10	40					30		—					—	2,410	2,900	3,640	—	—						
	12	36					26		20					26	1,900	2,270	2,840	2,830	3,400	4,245					
	13	38					27		22					27	2,130	2,550	3,190	3,070	3,680	4,605					
	15	40					17~75		6 8 10		18	40	20	M 5	8	4.4	30	24	30	2,220	2,660	3,340	3,170	3,800	4,755
	16	42									31	25					31	2,600	3,140	3,940	3,560	4,270	5,340		
	17	44	32	28				32			2,760	3,340					4,190	3,730	4,480	5,595					
	18	46	34	31				34			2,830	3,410					4,260	3,810	4,570	5,715					
	20	48	36	32				36			2,850	3,430					4,280	3,840	4,610	5,760					
	22	50	39	34				39			3,420	4,110					5,130	4,420	5,300	6,630					
	25	54	20~75	8 10 12 16	26	50	34	M 6	9.5	5.4	42	38	42	3,370	4,050	5,060	4,380	5,260	6,570						
	30	54			49	42					49	4,010	4,800	6,000	5,030	6,040	7,545								
	35	62			55	50					55	4,500	7,840	—	5,530	6,640	8,295								
	40	70			63	56					63	6,670	9,880	—	7,710	9,250	11,565								
	50	80			73	70					73	8,000	13,690	—	9,050	10,860	13,575								
	50	90			M10	14					9	—	—	—	—	—	—								

取付穴は、表・裏両方から取付けられるよう、タップ加工及びザグリ加工がされています。

<訂正用>

ラウンドタイプ
FXFB
PFXFB
SFXFB
コンパクトタイプ
FXEB
PFXEB
SFXEB