

赤枠内 L寸法指定範囲を修正

■軸径(D)固定タイプ

| H | 型式 | | L 指定0.01mm単位 | DC 指定0.005mm単位 | N 指定0.1mm単位 | SV 指定0.5mm単位 | ¥基準単価 1~4本 | | | | | | | | | | |
|----|--|-------|-----------------|--|----------------|-----------------|-----------------------|-------|-------|---------------|-------|---------------|-------|----------------------|-------|----------------------|--|
| | Type | D | | | | | GV-CPN-L GV-CPF-L | | | GV-CPD-L | | GV-CPX-L | | GV-CPK-L GV-CPG-L | | GV-CPP-L GV-CPH-L | |
| | | | | | | | DC・DCXの指定不要 (D=DC) | | | D=DC (DCX) | D≠DC | D=DC (DCX) | D≠DC | | | | |
| 2 | GV-CPX-L GV-CPH-L | 0.5 | 15.00~60.00 | | | | | — | — | 1,500 | — | — | 1,500 | 1,960 | | | |
| 3 | GV-CPN-L (D≥0.8) GV-CPF-L (D≥0.8) GV-CPD-L GV-CPX-L | 0.6 | 15.00~100.00 | $(D-0.08) \leq DC \leq D$ Ⓢ $D_{-0.02}^{0.01}$ の場合 DCの指定不可 | 0.3~10.0 | 2.0~50.0 | L-(2+SV+N)≥10 | — | — | 1,200 | 1,320 | — | — | 1,320 | 1,820 | | |
| | | 0.7 | | | | | | 1,190 | 1,270 | | | 1,270 | 1,770 | | | | |
| | | 0.8 | | | | | | 1,490 | 1,170 | 1,230 | 1,750 | 2,250 | 1,230 | 1,730 | | | |
| | | 0.9 | | | | | | 1,450 | 1,170 | 1,200 | 1,700 | 2,200 | 1,200 | 1,700 | | | |
| | | 1 | | | | | | 1,410 | 1,150 | 1,180 | 1,650 | 2,150 | 1,180 | 1,680 | | | |
| | | 1.2 | | | | | | 1,390 | 1,110 | 1,150 | 1,580 | 2,080 | 1,150 | 1,650 | | | |
| 4 | GV-CPX-L | 2 | 15.00~120.00 | Ⓢ DC=Dの場合 DCXと指定 | 0.5~15.0 | 2.0~60.0 | L-(2+SV+N)≥10 | — | — | 1,180 | 1,610 | 2,110 | 1,180 | 1,680 | | | |
| 5 | 1,400 | 1,130 | | | | | | 1,200 | 1,650 | 2,150 | 1,200 | 1,700 | | | | | |
| 6 | 1,410 | 1,170 | | | | | | 1,210 | 1,660 | 2,160 | 1,210 | 1,710 | | | | | |
| 7 | 1,420 | 1,180 | | | | | | 1,230 | 1,680 | 2,180 | 1,230 | 1,730 | | | | | |
| 8 | 1,450 | 1,210 | | | | | | 1,280 | 1,720 | 2,220 | 1,280 | 1,780 | | | | | |
| 9 | 1,470 | 1,230 | | | | | | 1,300 | 1,760 | 2,260 | 1,300 | 1,800 | | | | | |
| 10 | GV-CPG-L | 5 | 15.00~120.00 | | 0.5~15.0 | 2.0~60.0 | L-(2+SV+N)≥10 | 1,490 | 1,250 | 1,320 | 1,860 | 2,360 | 1,320 | 1,820 | | | |
| 11 | GV-CPP-L | 8 | | | | | | 1,750 | 1,280 | 1,460 | 2,070 | 2,570 | 1,460 | 1,960 | | | |
| 15 | GV-CPH-L | 10 | | | | | | 1,900 | 1,390 | 1,580 | 2,280 | 2,780 | 1,580 | 2,080 | | | |
| 18 | | 13 | | | | | | 2,290 | 1,630 | 1,920 | 2,850 | 3,350 | 1,920 | 2,420 | | | |