

P.677 (規格表)

D寸4のとき、Bは2になります。

型式		L 指定0.1mm単位	A	T	F	B	E	(d)	(N)	M (並目)	¥単価			
Type	D										CLBK	CLBKH	SCLBK	SCLBKH
CLBK CLBKH SCLBK SCLBKH	4	10.0~50.0	7	1.5	6	2	2	3.9	1.5	M3	440	540	660	830
	5	10.0~60.0	9			2.5		4.9		M4	450	570	690	870
	6	10.0~100.0	10					3		5.8	M5	470	590	720
	8		13		7.8	M6				610	720	870	1,090	
	10	15.0~100.0	16		4	3		9.8		M8	710	840	980	1,220
	12	15.0~200.0	18					11.8		M10	860	1,010	1,210	1,520
	13	25.0~200.0	24	18	12.8		M12	1,040		1,040	1,290	1,600		
	14				13.8			1,080		1,110	1,310	1,630		
	15				14.8			1,090		1,140	1,320	1,640		
	16				15.8			1,110		1,190	1,360	1,690		
	20	30.0~200.0	27	24	6	4	19.8	M16		1,450	1,580	1,770	2,210	
	25		30		8		5			24.8	2,850	3,100	4,550	5,370

<訂正用>

