

P寸・L寸・B寸指定タイプの(W)寸数値訂正

■P寸・L寸・B寸指定タイプ D寸T付サイズの特長：従来規格からねじ径を小さくし肉厚を厚くしました。D寸10T以上では、より短い取付部長さLの指定が可能です。

Type	型式 形状	D	D寸公差 g6	P 指定0.01mm単位	L 指定1mm単位	B 指定0.1mm単位	M (並目)	ℓ	(W)	<訂正用>			
FPQS GFPQS SFPQS HFPQS CFPQS	TA (丸)	6	-0.004 -0.012	4.00~ 6.00	8(9)~12	2.0~12.0	M3	5	1.5	1.5			
		6T					M2.6	4					
		8	-0.005 -0.014	6.00~ 8.00	11(12)~16	2.0~15.0	M5	8	1.8	1.8			
		8T					M4	6					
		10					M5	8					
		10T					M4	6					
	12	-0.006 -0.017	7.00~10.00	11(12)~20	3.0~20.0	M5	8	2.2	2.2				
	12T					M4	6						
	13					12~24	3.0~20.0			M5	8	2.5	2.5
	13T					8(12)~18				M4	6		
	16					13(14)~26	5.0~20.0			M8	10	3	3
	16T					10(14)~20				M6	9		
	20	16~32	5.0~20.0	M8	12	4	4						
	20T	10(14)~24		M6	9								
	-0.007 -0.020	13.00~20.00	20~40	5.0~20.0	M8	12	5	5					
			12(18)~30		M6	9							

ⓈL寸( )はダイヤ形状に適用 Ⓢ首下部の強度に注意 ⓈP.833